

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MasterTop TC 468 PART B  
Product code : 000000000050608359

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Product for construction chemicals  
Recommended restrictions on use : Industrial use, Professional use, Consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company : Master Builders Solutions  
Yapı Kimyasalları Sanayi ve Ticaret Ltd.  
Sti.,  
Ataşehir Kuzey, C Kapısı 3E/ 5-12  
34746 İstanbul, Turkey  
Telephone : +902162178800  
Telefax : +902162178800  
E-mail address of person responsible for the SDS : [mabas-eb@mbcc-group.com](mailto:mabas-eb@mbcc-group.com)

#### 1.4 Emergency telephone

ChemTel: +1-813-248-0585

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification T.R. SEA No 28848

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion/irritation, Category 2	H315: Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.

---

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

Specific target organ toxicity - single exposure, Category 3

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure, Category 2, Auditory organ

H373: May cause damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

#### Labeling T.R. SEA No 28848

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs (Auditory organ) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P271 Use only outdoors or in a well-ventilated area.  
P260 Do not breathe dust or mist.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist.  
P243 Take action to prevent static discharges.  
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.

#### **Response:**

P312 Call a POISON CENTER/ doctor/ .?/ if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version 1.0      Revision Date: 01.02.2021      SDS Number: 000000124355      Date of last issue: -  
Date of first issue: 01.02.2021

P314 Get medical advice/ attention if you feel unwell.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Additional Labeling:

EUH204 Contains isocyanates. May produce an allergic reaction.  
Do not keep the container sealed.

### 2.3 Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : isocyanate

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers	28182-81-2 500-060-2		<= 100
xylene	1330-20-7 215-535-7 601-022-00-9	Asp. Tox.1; H304 Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319	< 15

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version 1.0      Revision Date: 01.02.2021      SDS Number: 000000124355      Date of last issue: -  
Date of first issue: 01.02.2021

		STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	
1,6-hexamethylene diisocyanate	822-06-0 212-485-8 615-011-00-1		< 1
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7	Flam. Liq.3; H226 STOT SE3; H336	< 15
ethylbenzene	100-41-4 202-849-4 601-023-00-4	Asp. Tox.1; H304 Flam. Liq.2; H225 Acute Tox.4; H332 STOT RE2; H373 Aquatic Chronic3; H412	< 0,5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

Harmful if inhaled.  
May cause respiratory irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : no smoking Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.  
Keep away from heat. Avoid all sources of ignition: heat, sparks, open flame.

Further information on storage stability : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version 1.0      Revision Date: 01.02.2021      SDS Number: 000000124355      Date of last issue: -  
Date of first issue: 01.02.2021

### 7.3 Specific end use(s)

Specific use(s) : For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethylbenzene	100-41-4	TWA (8 Hour)	100 ppm 442 mg/m <sup>3</sup>	TR OEL
		Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.		
		STEL 15 min	200 ppm 884 mg/m <sup>3</sup>	TR OEL
		TWA	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	200 ppm 884 mg/m <sup>3</sup>	2000/39/EC
		STEL value	200 ppm 884 mg/m <sup>3</sup>	OEL (TR)
		TWA value	100 ppm 442 mg/m <sup>3</sup>	OEL (TR)
1-methoxy-2-propylacetate	108-65-6	TWA (8 Hour)	50 ppm 275 mg/m <sup>3</sup>	TR OEL
		Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.		
		STEL 15 min	100 ppm 550 mg/m <sup>3</sup>	TR OEL
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
		STEL value	100 ppm 550 mg/m <sup>3</sup>	OEL (TR)
		TWA value	50 ppm 275 mg/m <sup>3</sup>	OEL (TR)
xylene	1330-20-7	TWA (8 Hour)	50 ppm 221 mg/m <sup>3</sup>	TR OEL
		Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.		

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version 1.0      Revision Date: 01.02.2021      SDS Number: 000000124355      Date of last issue: -  
Date of first issue: 01.02.2021

		STEL 15 min	100 ppm 442 mg/m <sup>3</sup>	TR OEL
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		STEL value	100 ppm 442 mg/m <sup>3</sup>	OEL (TR)
		TWA value	50 ppm 221 mg/m <sup>3</sup>	OEL (TR)
xylene	1330-20-7	OEL	100 ppm 440 mg/m <sup>3</sup>	TRGS 900 (DE)
		TWA value	50 ppm 221 mg/m <sup>3</sup>	OEL (TR)
		STEL value	100 ppm 442 mg/m <sup>3</sup>	OEL (TR)
		MAC	100 ppm 435 mg/m <sup>3</sup>	MAK (TR)

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Respiratory protection in case of vapour/aerosol release.  
Suitable respiratory protection for higher concentrations or long-term effect:  
Gas filter for gases/vapours of organic compounds (boiling point <65 °C, f.e. EN 14387 Type AX)

Protective measures : Avoid inhalation of dusts/mists/vapours.  
Avoid contact with the skin, eyes and clothing.  
Avoid prolonged and/or repeated contact with the skin.  
Handle in accordance with good building materials hygiene and safety practice.



# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colourless to yellowish
Odor	:	solvent
pH	:	insoluble
Freezing point	:	approx. -48 °C
Boiling point	:	approx. 145 °C (1.013 hPa)
Flash point	:	38 °C Method: Flashpoint test using closed cup, determination of flashpoint.
Evaporation rate	:	not determined
Flammability (solid, gas)	:	Flammable.
Upper explosion limit / Upper flammability limit	:	For liquids not relevant for classification and labelling.
Lower explosion limit / Lower flammability limit	:	For liquids not relevant for classification and labelling.
Vapor pressure	:	approx. 10 hPa (20 °C) approx. 30 hPa (50 °C) approx. 37 hPa (55 °C)
Relative vapor density	:	not determined
Density	:	1,07 g/cm <sup>3</sup> (20 °C) Method: Paints and varnishes - Determination of Density
Solubility(ies) Water solubility	:	insoluble (20 °C)
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	approx. 460 °C Method: Mineral Oil Hydrocarbons; Determination of Ignition Temperature.
Decomposition temperature	:	Vapors may form explosive mixture with air.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : approx. 250 mPa.s (23 °C)  
Method: Polymers/resins in the liquid state or as emulsions or dispersions - Determination of viscosity using a rotational viscometer with defined shear rate (Annex A; coaxial-cylinder viscometers)

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : not fire-propagating

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with water, with formation of carbon dioxide.

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Amines  
Alcohols

### 10.6 Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Harmful if inhaled.

##### Product:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: other  
GLP: no data  
Remarks: The data on toxicology refer to the active ingredient.

Acute dermal toxicity : LD50 (Rabbit, male/female): > 2.000 mg/kg  
Method: other  
Test substance: Analogous: Assessment derived from products with similar chemical character.  
Remarks: The data on toxicology refer to the active ingredient.

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

##### Reproductive toxicity

Not classified based on available information.

##### STOT-single exposure

May cause respiratory irritation.

##### STOT-repeated exposure

Not classified based on available information.

##### Aspiration toxicity

Not classified based on available information.

##### Product:

No aspiration hazard expected.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

### Further information

**Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

#### Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

### 12.2 Persistence and degradability

**Product:**

Biodegradability : Inoculum: activated sludge  
Result: Not readily biodegradable (by OECD criteria).  
Biodegradation: 1 %  
Exposure time: 28 d  
Method: Closed bottle test

### 12.3 Bioaccumulative potential

**Components:**

#### 1,6-hexamethylene diisocyanate:

Partition coefficient: n- : Remarks: unmeasurable  
octanol/water

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.
- 

### SECTION 14: Transport information

#### 14.1 UN number

- ADN : UN 1866  
ADR : UN 1866  
RID : UN 1866  
IMDG : UN 1866  
IATA : UN 1866

#### 14.2 UN proper shipping name

- ADN : RESIN SOLUTION  
ADR : RESIN SOLUTION  
RID : RESIN SOLUTION  
IMDG : RESIN SOLUTION  
IATA : RESIN SOLUTION

#### 14.3 Transport hazard class(es)

- ADN : 3  
ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

- ADN  
Packing group : III  
Labels : 3

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

### ADR

Packing group : III  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

### RID

Packing group : III  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".

## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### 15.2 Chemical Safety Assessment

### SECTION 16: Other information

#### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs (/*_ORGAN_REPEAT\$/) through prolonged or repeated exposure.
H373	: May cause damage to organs (/*SAP_EHS_1023_043_ORGAN*/) through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
MAK (TR)	: Maximum Allowable Concentration (Turkey)
OEL (TR)	: Regulation on Protection of Health & Safety Measures from Risks related to Chemical Agents at Work (Turkey)
TR OEL	: Turkey. Chemical Agents at Work - Annex I: Indicative occupational exposure limit values
TRGS 900 (DE)	: TRGS 900 - Threshold limit values in the workplace air 'Luftgrenzwerte' (Publication by the German Federal Ministry of Labour and Social Affairs)

# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
MAK (TR) / MAC	:	Maximum allowable concentration:
OEL (TR) / STEL value	:	Short Term Exposure Limit (STEL):
OEL (TR) / TWA value	:	Time Weighted Average (TWA):
TR OEL / TWA (8 Hour)	:	Measured or calculated in relation to a reference period of eight-hour time-weighted average
TR OEL / STEL 15 min	:	A limit value above which exposure should not occur and is related to a 15-minute period, unless otherwise specified
TRGS 900 (DE) / OEL	:	Occupational Exposure Limit:

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### SDS Author

Name: Nazlı ÖZER  
Address: Master Builders Solutions Yapı Kimyasalları Sanayi ve Ticaret Ltd. Şti. 34746 Ataşehir - Istanbul, Turkey  
Phone: +90 262 751-6845  
Email: [nazli.ozer@mbcc-group.com](mailto:nazli.ozer@mbcc-group.com)  
Certificate no: KDU-A-0-0077  
Certification Date: 29.07.2020



# SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures; Part I".



## MasterTop TC 468 PART B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01.02.2021	000000124355	Date of first issue: 01.02.2021

---

Certificate Expiry Date: 29.07.2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN